Integration and Coordination of Multiple Tributary and Near-Shore Monitoring Efforts and the Use of Technology to Enhance these Efforts

Charles A. Peters
State of Lake Michigan 2011
September 27, 2011



Tributary and Near-Shore Monitoring Efforts

- Lake Michigan Monitoring Coordination
 Council Near Shore Monitoring work group
 (LMMCC NeMo)
- USGS GLRI Rivermouth and Tributary projects
- National Monitoring Network pilot project



LMMCC NeMo workgroup

- Members: Federal, State, Municipalities, Universities, and Non-profits
- Goals:
 - Understand and inventory nearshore monitoring activities (developing a web mapper);
 - coordinate implementation of a nearshore network;
 - identify monitoring gaps;
 - coordinate database approach;
 - develop a nearshore conceptual model;
 - integrate data reporting.




Examples of Lake Michigan Nearshore Activities

- USEPA National Coastal Assessment
- University and State near shore Buoys
- University and Federal near shore biology research
- USEPA Triaxus tows of nearshore zone
- USGS GLRI tributary, river mouth, beach, and near shore monitoring (9 projects)
- State and local tributary and river mouth (embayments) monitoring
- UWM sensors on Ferry crossings



USEPA National Coastal Condition Assessment in the Great Lakes






Grand Valley State Muskegon River Monitoring






UW-Milwaukee Buoys and Ferry Sensors













USEPA Lake Michigan 20 m contour Triaxus tow






Great Lakes Activities Web Mapping Application





Activities Data Entry System





USGS GLRI Activities Relative to the National Monitoring Network Design Resource Compartments

- Embayments
- GL Shallow Nearshore
- GL Medium Nearshore
- GL Offshore
- Rivers
- Ground Water
- Atmospheric Deposition
- Beaches
- Wetlands



Rivermouth Project Objectives

- Conceptual Model
- Classification

Characterization of Ecosystem Structure


and Function

Collaboratory





Rivermouth Conceptual Model





Rivermouth Classification



St. Louis River






Peshtigo River






Muskegon River

Characterization of Structure and Function









Monitoring Design - Rivers

- 59 NMN river sites toxic contaminant baseline
- 30 NMN river sites automated monthly plus high flow sample collection and continuous sensor measurements to forecast/nowcast contaminant loads
- 17 NMN river sites chemicals of emerging concern baseline
- 15 AOC sites Toxics in Sediments
- 8 NMN river sites pathogens and virus baseline





Tributary Monitoring Project Objectives


- Provide baseline information on contaminant loads at major Great Lakes tributaries,
- Provide quantifiable measures of restoration progress on major Great Lakes tributaries,
- Model potential load changes throughout the Great Lakes,



Determine Baseline of Toxic Contaminants

59 NMN sites sampled in fall of 2010


- POCIS (Polar Organic Chemical Integrative Sampler) monitor hydrophilic contaminants which could be potentially endocrine disrupting or acutely toxic
- **SPMD** (Semi-permeable membrane devices) designed to mimic biological membranes, such as the gills of fish.
- Water Samples for mercury and organic contaminants collected at time of installation. A 2nd sample collected in 2011.







30 NMN River sites instrumented for automated and continuous monitoring



Automated Sampling

- Analytes include:
 - suspended sediment, nutrients, chloride, and bacteria.
 - one sample per storm event will be analyzed for major ions.
 - Continuously sensed data: High Turbidity, Low Turbidity, Temperature, Conductivity, Dissolved Oxygen, pH
- Monthly base flow samples (12) plus eight storms will be sampled with 6 samples submitted per storm (60 environmental samples per site)
- Samples will be used to develop statistical relations between continuously measured parameters and lab analyzed parameters.







Real-time sensor monitoring information available at: http://waterwatch.usgs.gov/wqwatch/

Turbidity, water, unfiltered, monochrome near infra-red LED light, 780-900 nm, detection angle 90 +/ -2.5 degrees, formazin nephelometric units (FNU)

Most recent instantaneous value: 87 04-17-2011 12:30 EST







Real-time Water Quality Monitors

Directly measured

Computed or estimated

Gage Height/Stage Streamflow (discharge)

Specific Conductance


Chloride, alkalinity, fluoride, dissolved solids, sodium, sulfate, nitrate, atrazine

Turbidity

Total suspended solids, suspended sediment, fecal coliform, E. coli, total nitrogen, total phosphorus




Example of Real Time Surrogate





17 NMN River sites monitored for chemicals of emerging concern (PPCP - pharmaceuticals and personal care products)



Chemicals of Emerging Concern

- At 17 sites representing agricultural, urban and reference conditions. Ten of the which are located at AOCs.
 - Collect monthly and 6 storms samples (18 samples annually) for Pharmaceuticals and Personal Care Products




Determine Baseline of Toxic Contaminants in Sediments

At 15 AOC sites in the Great Lakes Sediment traps were installed

Analyzed for over 150 constituents:

- PAH's and Total PCB's
- Alkylated PAH's,
- Pharmaceuticals








Monitoring Tributaries for Pathogens and Viruses At 8 of the chemicals of

- At 8 of the chemicals of emerging concern sites (6 AOCs) collect samples every other month (base flow) and for 12 storms using an auto sampler:
 - Monitor for 8 human viruses, 10 bovine viruses, 3 bacterial pathogens, and cryptosporidium







Testing Automated Underwater Vehicles and CDOM Sensors


- Test Ecomapper AUV) in Milwaukee Harbor (2010), Green Bay, Sheboygan and Muskegon (2011)
- Chromophoric Dissolved Organic Matter (CDOM) sensors tested at tributary gages and deployed from a boat in embayments as a surrogate for toxic contaminants

Tie the river sensors and CDOM measurements to AUV work in the embayments, and Triaxus tow and buoy activities in the near shore, and to beach health monitoring.






AUV Example Output - Chlorophyl







Thank you





Questions?



Watershed modeling

- Identify current watershed modeling activities in the Great Lakes (in press)
- Develop HSPF models for 3 sub basins (Kalamazoo, Towanda, Bad), which are representative of the hydrogeology, physiography, land types, of a large region of the Great Lakes basin, and simulate water-quality processes
- Scenario development and comparison of results
 - Land—use changes
 - Management practices
 - Detention basins
 - Climate change



Land Cover Map of Three Watershed Modeling Basins



Hydro SPARROW

- Develop Hydro SPARROW a GIS link between SPARROW (a water-quality model) and WATER/PRMS (water-quantity models)
- Use Hydro SPARROW to provide an estimate of phosphorus and nitrogen loading to the Great Lakes under a variety of land use and climate change scenarios

